

REMARKS

This Preliminary Amendment cancels original claims 1 to 4, and adds new claims 5 to 8 in the underlying PCT Application No. PCT/DE03/02131. The new claims conform the claims to the U.S. Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.125, the Substitute Specification (including the Abstract, but without the claims) contains no new matter. The amendments reflected in the Substitute Specification (including the Title and Abstract) are to conform the Specification and Abstract to U.S. Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. § 1.121 and § 1.125, a Marked Up Version Of The Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. In the Marked Up Version, underlining indicates added text and "strike-throughs" and double-brackets indicate deleted text. Approval and entry of the Substitute Specification (including Abstract) is respectfully requested.

The underlying PCT Application No. PCT/DE03/02131 includes an International Search Report, dated November 28, 2003, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is asserted that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,
KENYON & KENYON

Dated: 4/19/05

By: 

Richard L. Mayer
Reg. No. 22,490

One Broadway
New York, New York 10004
Telephone: (212) 425-7200
Facsimile: (212) 425-5288

CUSTOMER NO. 26646

MULTIPLE FILAMENTS FOR SHEATHED-ELEMENT GLOW PLUGS

FIELD OF THE INVENTION

The present invention relates to a sheathed-element glow plug, in particular for internal combustion engines, composed essentially of a housing, a heating element situated on the housing and having a heating and regulating filament situated in the glow tube, current being applicable to this heating and regulating filament via a terminal stud situated in the housing.

~~Background Information~~BACKGROUND INFORMATION

Internal combustion engines, in particular diesel engines, need an additional heat source for preheating the gas mixture, the intake air, or the combustion chamber for starting and warm-up, in particular at low temperatures.

In passenger cars and sometimes in trucks, sheathed-element glow plugs ~~are usually~~ may be provided and used for this purpose. At least part of the heating element of such a sheathed-element glow plug protrudes into the combustion chamber of the engine and preheats the combustion chamber before the actual engine start and in cold run. In addition, the fuel may ignite on the hot surface of the sheathed-element glow plug.

Sheathed-element glow plugs ~~are usually~~ may be made of a plug housing having a glow tube or a tubular heating element situated thereon. A glow filament, embedded in a compacted magnesium oxide powder, is situated in the tubular heating

element made of a material resistant to corrosion by hot gases. The glow filament is usually made of two resistors connected in series: a control filament and a heating filament. The heating filament has an electrical resistance which is almost independent of the temperature, and the control filament is made of a material having a positive temperature coefficient (PTC). The heating filament is welded into the cap of the glow tube on the ground side for contacting, ~~it~~. The control filament is contacted to the terminal stud which is connected to the vehicle electrical system.

When a voltage is applied to the glow plug, most of the electric power is converted into heat in the heating filament, ~~and~~ and the temperature at the tip of the plug increases steeply. The temperature of the control filament, and thus also its resistance, increase with a time delay. Current consumption and thus the total power consumption of the sheathed-element glow plug are reduced and the temperature approaches a state of equilibrium. Currently sheathed-element glow plugs designed for 12 V to 24 V vehicle electrical systems are commercially available.

~~Object of the Invention~~

~~The object~~ SUMMARY OF THE INVENTION

An object of the exemplary embodiment and/or exemplary method of the present invention is to concentrate the heating power on the glow tube tip of the sheathed-element glow plug, making the latter also available for 42 V vehicle electrical systems.

~~Achievement of the Object~~

The ~~essence~~exemplary embodiment and/or exemplary method of the present invention ~~is to pack~~involves packing more heating wire and thus more electrical resistance into the same space using multiple filaments. Previously, typical sheathed-element glow
5 plugs have only had single coil filaments. In the sheathed-element glow plugs according to exemplary embodiment of the present invention, the heating filaments, the control filaments, or both, may have multiple coil filaments as required.

10 ~~Advantages of~~It is believed the invention

~~That an~~ advantage of packing more heating wire into a tight space is that the heating power may be increased, in
15 particular at the glow tube tip.

More wire in a tight space also means with respect to the heating and control filaments that a higher resistance is achieved and therefore higher voltages are made possible, in
20 particular for those designed for the planned 42-V vehicle electrical systems.

The filaments may be advantageously designed in different ways by producing the individual filaments wound in the same
25 direction or in opposite directions.

In particular when winding the filaments in opposite directions, the advantage is that the overall filament has a reduced outer diameter, and therefore a very compact design is
30 obtained, which also has the advantage that existing glow tubes do not need to be modified.

~~Additional advantageous embodiments become evident from the subsequent description, the drawing, and the claims.~~

Drawings

~~Figure 1~~ BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a section of a sheathed-element glow plug according to the present invention and having a multiple-coil heating filament at the glow tube tip.

Figure 2—shows an exemplary embodiment of a ~~possible~~ exemplary configuration of the multiple-coil heating filament illustrated in Figure 1.

Figure 3—shows a schematic diagram of the current flow in the multiple winding of the filaments illustrated in Figure 2, the filaments being wound in opposite directions.

Figure 4—shows a schematic top view of filaments wound in the same direction.

Figure 5—shows a schematic top view with the middle filament wound in the opposite direction.

Figure 6—shows a two-layer example with both filaments wound in the same direction.

Figure 7—shows a two-layer example with the two filaments wound in opposite directions.

~~Description of the Exemplary Embodiments~~

DETAILED DESCRIPTION

Figure 1 shows the structure of a sheathed-element glow plug 1. This sheathed-element glow plug 1 has a housing 2 and a glow tube 3 situated on the housing. A heating and control filament 4 is situated in glow tube 3, heating filament 5

being in the area of glow plug tip 6 and control filament 7 in the part above it. Heating and control filament 4 is supplied with power via a terminal stud 8.

5 ~~It is proposed according to the present invention and~~As depicted in Figure 1 ~~that~~, at least one part, either heating filament 5 or control filament 7, is a multiple-coil filament.

10 In the exemplary embodiment of Figure 1, heating filament 5 is a multiple-coil filament.

There are different embodiments for implementing the multiple winding of control filament 7 or heating filament 5.

15 Figure 2 shows an enlarged depiction of heating filament 5 illustrated in Figure 1. The manufacturing of heating filament 5 begins with a diameter d_1 , the other winding having a larger diameter such as d_2 being joined directly to the end of the first filament. The third filament having a diameter such as d_3 is joined to the end of filament 2, so that the current
20 flows as shown in Figures 3 and 4.

The filament layers may be wound in the same direction. In this case, the filaments cannot be wound as tightly, because
25 the individual filaments cross one another. The following inequality applies: $wd_3 > wd_2 + dd > wd_1 + dd$. Alternatively, the direction of winding may be inverted in each layer. In this case, the additional filament ~~is preferably~~may be in the groove of the adjacent filament. In this way, ~~it is possible~~
30 ~~to achieve~~ a smaller outer diameter may be achieved than in the case of the type of winding of Figure 2.

A high-performance sheathed-element glow plug is obtained by the simple multiple-coil design.

~~Abstract~~ABSTRACT OF THE DISCLOSURE

A sheathed-element glow plug, in particular for internal combustion engines, ~~is composed essentially of~~includes a housing, a glow plug situated on the housing and having a heating and regulating filament situated in the glow tube, current being applicable to this heating and regulating filament via a terminal stud situated in the housing. The control filament ~~(7) or~~the heating filament ~~(5) or the~~ heating and control filament ~~(4)~~ are optionally multiple-coil filaments.

~~(Figure 1)~~